

$\Phi 6.5\text{mm}$ Plastic 780nm Laser Module **$P_o < 1\text{mW}$** **Features**


1. APC (auto power control) IC inside
2. High quality PC lens
3. Low current consumption of the APC circuit
4. Superior laser beam profile

**Absolute maximum ratings**

Item	Symbol	Rating	Unit
Power supply voltage	V_{cc}	3.3	V
Laser Module optical output power	P_o	<1	mW
Operation temperature	T_{opr}	0~40	°C
Storage temperature	T_{stg}	0~60	°C


Electrical and optical characteristics ($T_c=25\text{ °C}$)

Item	Symbol	Min.	Typ.	Max	Unit	Condition
Wavelength	λ	-	785	-	nm	$P_o = 1\text{mW}$
Operation current	I_{op}	-	-	35	mA	$P_o = 1\text{mW} V_{cc}=3\text{V}$
Operation voltage	V_{op}	2.5	-	3.3	Volt	
Laser Beam spot size at 10m				<20mm		
Divergence angle				2 mrad		
Mean time to failure (MTTF) 25°C				>10000 hrs		

Outline dimensions (Units: mm)**Laser Safety Precautions**

1. Do not look into the laser beam directly by eyes. The laser beam may cause severe damage to human eyes.
2. Optical Lens is made of plastic or glass. Do not contaminate lens by soiling, oil or chemical..

PIN Assignment:




A type : Heat sink stand (-)

Pin 1 : Vcc

Pin 2 : GND

Pin 3 : NC (No external connection)




B type :Heat sink stand (+)




Instruction manual

1. DC Power connection mode 1

A type : Heat sink stand (-)



B type :Heat sink stand (+)



2. DC Power connection mode 2

